



# BRADFORD GOLD™ SKILLION ROOF BLANKET

## Introduction

Bradford Gold's new R2.9, 115mm thick skillion roof blanket has been designed to be used within a 140mm rafter whilst retaining your airspace.

Insulation thickness within skillion roof design has been an ongoing issue for specifiers. Bradford Gold™ skillion roof blanket has been designed as an economical solution to fit 140mm and 190mm rafters, while maintaining a 25mm air gap.

This not only provides Architects with more design flexibility, but also saves money on the cost of unnecessary timber.

## Product Description

Bradford Blanket insulation is a lightweight, compressible insulation material manufactured from the controlled felting of recycled glass, bonded together using a thermosetting resin. The product can be identified by its light golden appearance.

Bradford Gold skillion roof blanket is an economical solution to fit 140mm and 190mm rafters, while achieving R-Values of 2.9, 3.2 and 3.6 respectively.

## Applications

The Bradford Gold skillion roof blanket range has been designed to exceed H1 compliance, (based on the use of the schedule method) whilst still maintaining the 25mm air gap required from the top of the insulation to the underside of the roofing underlay.

## Features & Benefits

- Bradford Gold is manufactured using the latest Arlanda fibre technology, making Bradford Gold products nicer to handle, cut and install, while providing superior performance
- Bradford Gold has a 75 year proud history in providing the very best insulation to the Australasian building industry
- Will not settle over time
- All Bradford Gold products are guaranteed for the life of the building
- Naturally resistant to insect and vermin attack
- Non-carcinogenic and provides excellent indoor air quality
- 100% bio-soluble - low irritant and low allergen
- Bradford Gold achieves the best possible fire ratings. Bradford Gold will not ignite or burn and can hinder the spread of flame.

## Standard Sizes & Packaging

R - Value	Dimensions (mm)	Thickness (mm)	Area/Roll (m <sup>2</sup> )	Type	Rafter Size * (mm)
R2.9	8m x 1200	115	9.6	Skillion / Ceiling	140
R3.2	10m x 1200	145	12	Skillion / Ceiling	190
R3.6**	7.5m x 1200	165	9	Skillion / Ceiling	190

\* Recommended rafter size allowing a 25mm air gap

\*\* Special order

# BRADFORD GOLD™ SKILLION ROOF BLANKET

## Formulation

Bradford's advanced manufacturing processes provides products that are safe for allergy sufferers, allowing you and your family to breathe easy with added piece of mind.

Bradford products are manufactured using the latest FBS-1 bio-soluble formulation which has been assessed as non-hazardous under the National Occupational Health and Safety Commission's guidelines and can be installed with absolute confidence.



Bradford glasswool products also do not contain harmful VOC's – Volatile Organic Compounds; they do not contain any harmful amounts of formaldehyde or other organic chemicals.

## Designing for Sustainability

Bradford Gold is manufactured from up to 65% recycled glass. Much of the recycled content used is not suitable for recycling in other applications. All water used in the manufacturing of our glasswool products is also recycled.

## Zero Ozone Depleting Potential

Bradford Insulation has undertaken an audit of our Glasswool, Rockwool and reflective foil laminate insulation manufacturing processes referencing the US EPA List of Ozone Depleting Substances (Class 1 and Class 2). This audit found that no ozone depleting substances are involved in either the manufacture or composition of these products.

## Physical Properties

Property	Performance	Test Criteria
Maximum Service Temperature	350 °C	Where high temperature use is required please seek advice from Bradford
Flow Resistivity	0.5 x 10 <sup>4</sup> mks Rayls/m	
Fire Resistance	Ignitability 0 Heat Evolved 0 Spread of Flame 0 Smoke developed 0	When tested in accordance with AS/NZS1530.3:1999
Corrosion Resistance	pH 7.5 – 8.0	When tested in accordance with BS 3958 Part 5 - 1986
Moisture Absorbance	Less than 0.2% by volume	When left in a controlled atmosphere of 50 °C and 95% relative humidity for four days

**Bradford™**  
for smarter environments

CSR Bradford Insulation  
111b Kerwyn Ave, PO Box 204115, Highbrook, Manukau 2161, Auckland  
Telephone (+64) 9 968 2160 Facsimile (+64) 9 968 2199 Freephone 0800 277 123

[www.bradfordinsulation.co.nz](http://www.bradfordinsulation.co.nz)

CSR Bradford Insulation is a business division of CSR Building Products Limited ABN 55 008 631 356

The contents of this brochure are copyright protected and may not be reproduced in any form without prior written consent of CSR Bradford Insulation. Recommendations and advice regarding the use of the products described in this brochure are to be taken as a guide only, and are given without liability on the part of the company or its employees. We reserve the right to change product specifications without prior notification, please refer to the Bradford website for the latest version of this document. The purchaser should independently determine the suitability of the product for the intended use and application.

BRADFORD GOLD™ SKILLION ROOF BLANKET - DATA SHEET

**CSR**